





- ride
- **(**; Thermostatically controlled cooling system for consistent engin temperature
- Stainless steel water pump housing for outstanding durability
- High grade marine aluminum alloy that provides the ultimate protection
- against corrosion
  Zinc coating on internal water
  passages for superior corrosio **(**; resistance
- **(**; Aluminum propelli
- Hour metering for easy maintenance record

## Speçifications

m	
MODEL	т9.8
Туре	2 Stroke
Maximum output (kw)	7.2
Dimensions (mm)	S: 793*320*996 L: 793*320*1123
Weight (kg)	S: 26 L: 27
Maximum operating range(rpm)	5000-6000
Number of cylinder	2
Bore x Stroke(mm)	50 x 43
Displacement (cc)	169
Engine lubrication system	Premixed Fuel
Cooling system	Water/Thermostatic Control
Starting system	Manual Start
Ignition	CDI
Fuel tank capacity(L)	12L
Speed control	Twist grip type
Gear ratio	2.08 (27:13)
Gear Shift	F-N-R

▲ Due to CalonGloria's ongoing commitment to product improvement, we the right to change without notice, equipment, materials, or specifications.

## CALON GLORIA MOTOR FEATURES

- Description to be before the collection of the c
- \*) Overheating protection If the inlet is blocked, the machine is hot. The cylinder head is equipped with a temperature controlled sensor. If the temperature is too high, the automatic speed limit will not work properly and the machine will not be damaged.
- Carburetor improvement Anti corrosion for carburet engines will be more stable.
- 5 layers paint 5 layers paint for a protection.
- - Anti-noise system

    New improvement on the anti-noise system for exhaust control. It's a quiet
- - New design for exhaust system More preciously temperature control with the new design on exh
- - \$) Upgraded oil piper
    Anti-aging upgraded oil piper, pressure test over 8/4kg, tensile strength over
    8MPA and the elongation at break is over 200%

  - Automatic positioning system
     Automatic positioning system tilt through the operation