



HOT SHEET



- Great for car toppers, so inflatables and tenders all fishing rigs
 - High grade marine aluminum alloy that provides the ultimate protection against
 - CDI ignition provides automatic sp advance to provide maximum power throughout the whole APM range
 - Loop charging boosts power and fuel efficiency Comes standard with shallo drive, an extremely useful feature when tackling rivers, estuaries and
- creeks. Truly five layers of paint, good corrosic



M/	
MODEL	T15
Туре	2 Stroke
Maximum output (kw)	11
Dimensions (mm)	S:873*332*1043 L:873*332*1170
Weight (kg)	S: 36 L:37.5
Maximum operating range(rpm)	4500-5500
Number of cylinder	2
Bore x Stroke(mm)	56 x 50
Displacement (cc)	246
Engine lubrication system	Premixed Fuel
Cooling system	Water/Thermostatic Control
Starting system	Manual Start
Ignition	CDI
Fuel tank capacity(L)	24
Speed control	Twist grip type
Gear ratio	2.08 (27:13)

[▲] Due to CalonGloria's ongoing commitment to product improvement, the right to change without notice, equipment, materials, or specificati

CALON GLORIA MOTOR FEATURES

▶ Overspeed protection
If the machine is running, the engine speed exceeds the specified speed value, the machine speed limit protection device will automatically limit the speed, to prevent engine overheating caused by engine damage

▶ Low oil pressure warning When the oil pressure drop drops automatically

Diverheating protection
If the inlet is blacked, the machine is hat. The cylinder head is equipped with a
temperature-controlled sensor. If the temperature is too high, the automatic
speed limit will not work properly and the machine will not be damaged.

Carburetor improvement Anti corrosion for carbureto engines will be more stable. nt on the idle jet to main jet.

5 layers paint 5 layers paint for a

Anti-naise system ew improvement on the anti-r st control it's a q

New design for exhaust system re preciously temperature control with the ne

ti-aging upgraded oil piper, pressure test over 0/4kg, tensil PA and the elangation at break is over 200%

Automatic positioning system utomatic positioning system tilt through the elastic locker. m peration