



and reliability.

HOT SHEET T40



This is the two stroke o series developed mainly for commercial use such as on fishing and passenger ssels. This series suits harsh conditions that include everyday use and situations avolving long hours of continuous operation. Enhanced strength and durability in locations. uch as roller bearings, crankshaft and cylinder block, as well as an improved water pump that ensures plenty of cooling effect, combine to deliver substantial improvements in durability

# Specifications

MODEL	T40 ENDURO
Туре	2 Stroke
Maximum output (kw)	29.4
Dimensions (mm)	1073*402*1364
Weight (kg)	73.6
Maximum operating range(rpm)	4500-5500
Number of cylinder	2
Bore x Stroke(mm)	80 x 70
Displacement (cc)	703
Engine lubrication system	Premixed Fuel
Cooling system	Water/Thermostatic Control
Starting system	Manual Start
Ignition	CDI
Fuel tank capacity(L)	24
Speed control	Twist grip type
Gear ratio	26:13
Gear Shift	F-N-R

### CALON GLORIA MOTOR FEATURES

## f the machin

ropeller(in.)

rspeed protection machine is running, the engine speed exceeds the specified speed value, suchine speed limit protection device will automatically limit the speed, to it engine overheating caused by engine damage

11 1/8\*13

Low oil pressure warnin When the oil pressure drop Props automatically

Diverheating protection
If the inlet is blacked, the machine is hat. The cylinder head is equipped with a
temperature-controlled sensor. If the temperature is too high, the automatic
speed limit will not work properly and the machine will not be damaged.

Carburetor improvement

Anti corrosion for carbureto
engines will be more stable. ent on the idle jet to main jet.

st control it's a q

lew design for exhaust system e preciously temperature control with the no

iging upgraded oil piper, pressure test over 0/4kg, tensil and the elangation at break is over 200%